



PIN	SYMBOL
1	VSS
2	VDD
3	V0
4	RS
5	RW
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	CS1
16	CS2
17	RST
18	VEE
19	LED-A(+5V)
20	LED-K

**SPECIFICATIONS:**

- 1. DISPLAY TYPE: STN / POSITIVE (YELLOW-GREEN) / TRANSFLECTIVE
- 2. DRIVE IC: AIP31107,AIP31108 or EQV.
- 3. CONNECTOR: ZEBRA
- 4. OPERATING VOLTAGE: VOP = 8.75 V, VDD = 5.0V
- 5. OPERATING TEMPERATURE: -20 ~ 70°C
- 6. STORAGE TEMPERATURE: -30 ~ 80°C
- 7. DRIVE MODE: 1/64 DUTY, 1/9 BIAS
- 8. VIEWING ANGLE: 6 O'CLOCK
- 9. BACKLIGHT: YELLOW-GREEN LED, I = 60mA
- 10. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

**BOCEN DISPLAY TECHNOLOGY CO., LTD.**

DESIGNED BY: Shawn	<b>BB12864-07</b>	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: <a href="http://www.bocentech.com">http://www.bocentech.com</a>		DATE: 2011-8-20