



PIN	SYMBOL
1	NC
2	CSB
3	RSTB
4	A0
5	WR
6	RD
7	D0
8	D1
9	D2
10	D3
11	D4
12	D5
13	D6
14	D7
15	VDD
16	VSS
17	NC
18	NC
19	V0
20	XV0
21	NC
22	VM0
23	NC
24	NC
25	NC
26	NC
27	VG
28	NC
29	C86
30	PSB
31	NC
32	NC



SPECIFICATIONS:

- 1. DISPLAY TYPE: STN / BLUE / NEGATIVE / TRANSMISSIVE
- 2. DRIVE IC: ST7567
- 3. OPERATING VOLTAGE: Vlcd=6.5V; Vdd=3.3V
- 4. OPERATING TEMPERATURE: 0°C ~ +50°C
- 5. STORAGE TEMPERATURE: -20°C ~+70°C
- 6. DRIVE MODE: 1/32DUTY, 1/6BIAS
- 7. BACKLIGHT: 4PCS WHITE LED, IF=60mA, VF=3.0V
- 8. VIEWING ANGLE: 6 O'CLOCK
- 9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn	BG12232-01	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2019-06-11