



PIN	SYMBOL
1	/CS1
2	/RES
3	A0
4	R/W(/WR)
5	E(/RD)
6	DB0
7	DB1
8	DB2
9	DB3
10	DB4
11	DB5
12	DB6
13	DB7
14	VDD
15	VSS
16	NC
17	NC
18	NC
19	NC
20	NC
21	VO
22	XV0
23	NC
24	NC
25	VG
26	NC
27	NC
28	NC
29	NC
30	NC
31	C86
32	P/S
33	NC
34	NC

SPECIFICATIONS:

- 1. DISPLAY TYPE: FSTN / POSITIVE / TRANSFLECTIVE
- 2. DRIVE IC: ST7567
- 3. OPERATING VOLTAGE: VOP = 9.8V, VDD = 3.3V
- 4. OPERATING TEMPERATURE: -30 ~ +80°C
- 5. STORAGE TEMPERATURE: -35 ~ +85°C
- 6. DRIVE MODE: 1/65 DUTY, 1/9 BIAS
- 7. VIEWING ANGLE: 6 O'CLOCK
- 8. BACKLIGHT: 8PCS WHITE LED, IF =90mA, VF =3.5V
- 9. CUSTOMER PART NO.: BOCEN STANDARD PRODUCT

BOCEN DISPLAY TECHNOLOGY CO., LTD.

DESIGNED BY: Shawn	BG12864-17	VERSION: 1.0
CHECKED BY: William		NO.: 1 OF 1
APPROVED BY: Rio		UNIT: mm
Website: http://www.bocentech.com		DATE: 2018-12-24