

## STANDARD OLED DISPLAY MODULE

Update: 2025/10/16

No.	Size	Bocen Part Number	Resolution	Panel Size (mm)	Viewing Area (mm)	Active Area (mm)	PINs	Color	Porwer Supply Voltage	Driving Voltage	Operating Temperature	Storage Temperature	Drive IC	Interface
1	0.42"	BO7240-01-SWG16P042	72x40	12.00x11.00x1.23	10.196x6.18	9.196x5.18	16	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-WIRE SPI /I2C
		BO7240-03-SWG16P042												
		BO7240-07-SWG16P042												
		BO7240-08-SWG16P042												
		BO7240-09-SWG16P042												
		BO7240-11-SWG16P042												
		BO7240-12-SWG16P042												
		BO7240-15-SWG16P042												
		BO7240-16-SWG16P042												
		BO7240-19-SWG16P042												
BO7240-20-SWG16P042														
BO7240-21-SWG16P042														
BO7240-23-SWG16P042														
BO7240-25-SWG16P042														
BO7240-29-SWG16P042														
2	0.42"	BO7240-26-SWG8P042	72x40	12.00x11.00x1.23	10.196x6.18	9.196x5.18	8	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-WIRE SPI /I2C
		BO7240-28-SWG8P042												
		BO7240-31-SWG8P042B												
3	0.42"	BO7240-00-SWG12P042	72x40	12.00x11.00x1.23	10.196x6.18	9.196x5.18	12	Monochrome (White)	/	/	-40~70°C	-40~85°C	SSD1306BZ	4-WIRE SPI /I2C
		BO7240-18-SWG12P042												
		BO7240-27-SWG12P042												
4	0.49"	BO6432-00-SWG14P049	64x32	14.50x11.60x1.23	12.58 x 6.98	11.18x5.58	14	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	I2C
5	0.66"	BO6448-00-SWG28P066	64x48	18.46x18.10x1.21	15.42x12.06	13.42x10.06	28	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	6800/8080 Interface I2C / 4-wire SPI
		BO6448-29-SWG28P066												
6	0.66"	BO6448-27-SWG11P066	64x48	16.42x16.90x1.23	14.42x11.06	13.42x10.06	11	Monochrome (White)	/	/	-40~70°C	-40~85°C	SSD1315	I2C
BO6448-28-SWG11P066														
7	0.68"	BO9632-01-SWG15P068	96x32	19.80x9.92x1.23	17.70x6.82	16.30x5.42	15	Monochrome (White)	1.65~3.3V	3.5~4.2V	-20~70°C	-30~80°C	SSD1306	4-wire SPI
8	0.69"	BO9616-01-SWG14P069	96x16	26.30x8.00x1.23	18.86x4.78	17.26x3.18	14	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	I2C
		BO9616-02-SWG14P069												
		BO9616-04-SWG14P069												
		BO9616-06-SWG14P069												
		BO9616-10-SWG14P069												
		BO9616-11-SWG14P069												
		BO9616-15-SWG14P069B												
		BO9616-17-SWG14P069												
BO9616-30-SWG14P069C														
9	0.69"	BO9616-05-SWG8P069	96x16	26.30x8.00x1.23	18.86x4.78	17.26x3.18	8	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	I2C
		BO9616-16-SWG8P069												
		BO9616-20-SWG8P069												
		BO9616-21-SWG8P069												
		BO9616-31-SWG8P069C												
10	0.78"	BO80128-03-HWG13P078	48x64	13.90x22x1.23	12.14x16.30	10.54x14.70	13	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	I2C
		BO80128-07-HWG13P078												
		BO80128-09-HWG11P078												
11	0.78"	BO80128-09-HWG11P078	48x64	13.90x22x1.23	12.14x16.30	10.54x14.70	11	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	I2C
BO80128-06-HWG12P078														
12	0.78"	BO80128-06-HWG12P078	48x64	13.90x22x1.23	12.14x16.30	10.54x14.70	12	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	I2C
BO80128-03-HWG15P084														
13	0.84"	BO64128-03-HWG15P084	64X128	12.8x25.3x1.22	10.58x20.18	9.58x19.18	15	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1107	4-wire SPI

# STANDARD OLED DISPLAY MODULE

Update: 2025/10/16

No.	Size	Bocen Part Number	Resolution	Panel Size (mm)	Viewing Area (mm)	Active Area (mm)	PINs	Color	Porwer Supply Voltage	Driving Voltage	Operating Temperature	Storage Temperature	Drive IC	Interface
14	0.87"	BO12832-00-SWG15P087 BO12832-13-SWG15P087 BO12832-63-SWG15P087 BO12832-66-SWG15P087 BO12832-68-SWG15P087 BO12832-73-SWG15P087 BO12832-77-SWG15P087 BO12832-83-SWG15P087 BO12832-89-SWG15P087 BO12832-92-SWG15P087 BO12832-93-SWG15P087	128x32	29.00x8.70x1.22	22.856x6.824	21.356x5.324	15	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1316Z	4-wire SPI
15		BO12832-61-SWG8P087 BO12832-64-SWG8P091	128x32	29.00x8.70x1.22	22.856x6.824	21.356x5.324	8	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1316Z	4-wire SPI
16		BO12832-29-SWG13P087	128x32	29.00x8.70x1.22	22.856x6.824	21.356x5.324	13	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1316Z	4-wire SPI
17	0.91"	BO12832-05-SWG14P087 BO12832-46-SWG14P087 BO12832-58-SWG14P087 BO12832-60-SWG14P087 BO12832-62-SWG14P087 BO12832-70-SWG14P087 BO12832-79-SWG14P087	128x32	29.00x8.70x1.22	22.856x6.824	21.356x5.324	14	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1316Z	I2C
18		BO12832-01-SWG14P091 BO12832-32-SWG14P091 BO12832-38-SWG14P091 BO12832-91-SWG14P091 BO12832-99-SWG14P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	14	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	I2C
19		BO12832-30-SBG4P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	4	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI
20		BO12832-42-HWG11P091B	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	11	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	I2C
21		BO12832-47-SWG8P091 BO12832-64-SWG8P091 BO12832-71-SWG8P091 BO12832-90-SWG8P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	8	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	I2C
22		BO12832-02-SBG12P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	12	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI
23		BO12832-96-SWG12P091 BO12832-97-SWG12P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	12	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI
24		BO12832-80-SWG11P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	11	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	
25		BO12832-78-SWG10P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	10	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI
26		BO12832-49-SWG20P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	20	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI
27	0.91"	BO12832-03-SWG15P091 BO12832-56-SWG15P091 BO12832-04-SWG15P091 BO12832-18-SWG15P091 BO12832-59-SWG15P091 BO12832-67-SWG15P091 BO12832-72-SWG15P091 BO12832-76-SWG15P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	15	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI

# STANDARD OLED DISPLAY MODULE

Update: 2025/10/16

No.	Size	Bocen Part Number	Resolution	Panel Size (mm)	Viewing Area (mm)	Active Area (mm)	PINs	Color	Porwer Supply Voltage	Driving Voltage	Operating Temperature	Storage Temperature	Drive IC	Interface
28	0.91"	BO12832-50-SWG4P091 BO12832-51-SWG4P091 BO12832-65-SWG4P091 BO12832-74-SWG4P091 BO12832-81-SWG4P091 BO12832-82-SWG4P091 BO12832-86-SWG4P091 BO12832-95-SWG4P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	4	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI
29		BO12832-06-SBG15P091 BO12832-57-SBG15P091 BO12832-07-SBG15P091	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	15	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI
30		BO12832-08-SBG14P091 BO12832-87-SBG14P091 BO12832-88-SBG14P091 BO12832-94-SBG14P091	128x32	29.00x8.70x1.22	22.856x6.824	21.356x5.324	14	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	I2C
31		BO12832-100-SWG4P091	128x32	38.00x12.00x3.527	24.384x7.584	22.384x5.584	4	Monochrome (White)	3.3~5.0V	/	-40~70°C	-40~85°C	SSD1306BZ	I2C
32	0.95"	BO9664-01-SCG23P095	96x64	25.70x22.20x1.45	22.14x15.42	20.14x13.42	23	Color			-40~70°C	-40~85°C	SSD1331Z	
33	0.96"	BO12864-00-SBG30P096 BO12864-05-SBG30P096 BO12864-09-SBG30P096 BO12864-205-SBG30P096 BO12864-21-SBG30P096	128x64	26.70x19.26x1.41	23.74x12.864	21.744x10.864	30	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	6800/8080 Interface I2C / 4-wire SPI
34		BO12864-04-SDG30P096 BO12864-29-SDG30P096	128x64	26.70x19.26x1.41	23.74x13.20	21.74x11.20	30	Monochrome (Yellow & Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	6800/8080 Interface I2C / 4-wire SPI
35		BO12864-03-SWG30P096 BO12864-02-SWG30P096 BO12864-06-SWG30P096 BO12864-07-SWG30P096 BO12864-37-SWG30P096 BO12864-40-SWG30P096 BO12864-43-SWG30P096 BO12864-62-SWG30P096 BO12864-120-SWG30P096 BO12864-139-SWG30P096 BO12864-142-SWG30P096 BO12864-143-SWG30P096	128x64	26.70x19.26x1.41	23.74x12.864	21.744x10.864	30	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	6800/8080 Interface I2C / 4-wire SPI
36		BO12864-175-SWG30P096 BO12864-187-SWG30P096 BO12864-188-SWG30P096 BO12864-189-SWG30P096 BO12864-218-SWG30P096 BO12864-230-SWG30P096 BO12864-239-SWG30P096 BO12864-252-SWG30P096	128x64	26.70x19.26x1.41	23.74x12.864	21.744x10.864	30	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	6800/8080 Interface I2C / 4-wire SPI
37		BO12864-180-SWG11P096	128x64	26.70x19.26x1.41	23.74x13.20	21.74x11.20	11	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	4-wire SPI
38		BO12864-191-SDG12P096	128x64	26.70x19.26x1.41	23.74x13.20	21.74x11.20	12	Monochrome (Yellow & Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	4-wire SPI
39		BO12864-224-SWG12P096 BO64128-27-HWG12P096 BO64128-32-HWG12P096 BO64128-43-CWG12P096D	128x64	26.70x19.26x1.41	23.74x13.20	21.74x11.20	12	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	4-wire SPI
40		BO12864-185-SBG14P096	128x64	24.74x16.90x1.42	22.74x11.86	21.744x10.864	14	Monochrome (Yellow & Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	4-wire SPI
41		BO12864-137-SBG20P096	128x64	24.74x16.90x1.42	22.74x11.86	21.744x10.864	20	Monochrome (Yellow & Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	I2C// 3/4-wire SPI

# STANDARD OLED DISPLAY MODULE

Update: 2025/10/16

No.	Size	Bocen Part Number	Resolution	Panel Size (mm)	Viewing Area (mm)	Active Area (mm)	PINs	Color	Porwer Supply Voltage	Driving Voltage	Operating Temperature	Storage Temperature	Drive IC	Interface	
42	0.96"	BO12864-167-SDG15P096	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	15	Monochrome (Yellow & Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI	
43		BO12864-257-SBG15P096	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	15	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI	
44		BO12864-240-SWG18P096	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	18	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI	
45		BO12864-34-SBG20P096	128x64	24.74x16.90x1.42	22.74x11.86	21.744x10.864	20	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	I2C// 3/4-wire SPI	
46		BO12864-01-SWG20P096 BO12864-16-SWG20P096 BO12864-61-SWG20P096 BO12864-66-SWG20P096 BO12864-67-SWG20P096 BO12864-81-SWG20P096 BO12864-193-SWG20P096 BO12864-196-SWG20P096 BO12864-215-SWG20P096 BO12864-251-SWG20P096	128x64	24.74x16.90x1.42	22.74x11.86	21.744x10.864	20	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	I2C// 3/4-wire SPI	
47		BO12864-197-SWG24P096 BO12864-213-SWG24P096 BO12864-242-SWG24P096 BO64128-31-HWG24P096	128x64	24.74x16.90x1.42	22.74x11.86	21.744x10.864	24	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	4-wire SPI	
48		BO64128-01-HWG13P096 BO64128-10-HWG13P096 BO64128-19-CWG13P096D BO64128-26-HWG13P096 BO64128-30-HWG13P096 BO64128-36-HWG13P096 BO64128-38-HWG13P096 BO64128-39-HWG13P096 BO64128-40-HWG13P096	128x64	24.74x16.90x1.42	22.74x11.86	21.744x10.864	13	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	4-wire SPI	
49		BO12864-08-SWG14P096 BO64128-18-HWG14P096	128x64	24.74x16.90x1.42	22.74x11.86	21.744x10.864	14	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	4-wire SPI	
50		BO12864-60-SWG15P096 BO12864-74-SWG15P096 BO12864-124-SWG15P096 BO12864-216-SWG15P096 BO64128-00-HWG15P096	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	15	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	4-wire SPI	
51		BO12864-31-SBG15P096	128x64	30.00x11.50x1.23	24.384x7.584	22.384x5.584	15	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1315Z	4-wire SPI	
52		BO12864-108-SWG7P096	128x32	30.00x11.50x1.23	24.384x7.584	22.384x5.584	7	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI	
53		BO12864-109-SBG4P096 BO12864-146-SBG4P096	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	4	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI	
54		BO12864-182-SDG4P096 BO12864-208-SDG4P096	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	4	Monochrome (Yellow & Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI	
55		BO12864-99-SWG4P096 BO12864-172-SWG4P096 BO12864-73-SWG4P096 BO12864-201-SWG4P096 BO12864-237-SWG4P096	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	4	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI	
56		BO12864-10-SWG4P096+PCB BO12864-10A-SWG4P096+PCB	128x64	27.50x27.80x2.61	23.74x12.87	21.75x10.86	4+30	Monochrome (White or Blue)			-40~70°C	-40~85°C	SSD1306		
57		BO12864-183-SWG8P096 BO64128-42-CWG8P096D	128x64	27.50x27.80x2.61	23.74x12.87	21.75x10.86	8	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI	
58		BO64128-01-HWG13P096	64x128	14.00x28.00x1.23	11.86x22.74	10.86x21.74	13	Monochrome (White)	2.6~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1107	I2C/ 4-wire SPI	
59		1.1"	BO19696-01-SWG14P110	196x96	29x17.7x1.135	26.02x12.21	25x11.21	14	Monochrome (White)	2.6~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1357Z	4-wire SPI

# STANDARD OLED DISPLAY MODULE

Update: 2025/10/16

No.	Size	Bocen Part Number	Resolution	Panel Size (mm)	Viewing Area (mm)	Active Area (mm)	PINs	Color	Porwer Supply Voltage	Driving Voltage	Operating Temperature	Storage Temperature	Drive IC	Interface
60	1.29"	BO12864-243-HWG12P129 BO12864-235-HWG12P129	128x64	35.8x17.1x1.43	30.42x15.7	29.42x14.70	12	Monochrome (White)	2.6~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1105	I2C/ 4-wire SPI
61		BO12864-133-HWG16P129 BO12864-202-HWG16P129	128x64	35.8x17.1x1.43	30.42x15.7	29.42x14.70	16	Monochrome (White)	2.6~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1105	I2C/ 4-wire SPI
62	1.3"	BO12864-24-HWG16P130 BO12864-207-HWG16P130 BO12864-222-HWG16P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	16	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1106G	6800/8080 Interface I2C / 4-wire SPI
63		BO64128-05-HWG12P130 BO64128-11-HWG12P130 BO64128-37-HWG12P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	12	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1106G	6800/8080 Interface I2C / 4-wire SPI
64		BO64128-09-HWG13P130 BO64128-29-HWG13P130 BO64128-34-HWG13P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	13	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1107	6800/8080 Interface I2C / 4-wire SPI
65		BO64128-33-HWG10P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	10	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1107	6800/8080 Interface I2C / 4-wire SPI
66		BO12864-134-HBG16P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	16	Monochrome (Yellow & Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1106G	6800/8080 Interface I2C / 4-wire SPI
67		BO12864-209-HWG14P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	14	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1106G	6800/8080 Interface I2C / 4-wire SPI
68		BO12864-220-HBG14P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	14	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1106G	6800/8080 Interface I2C / 4-wire SPI
69		BO12864-199-HWG24P130 BO12864-200-HBG24P130 BO12864-227-HWG24P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	24	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1106G	6800/8080 Interface I2C / 4-wire SPI
70		BO12864-96-HWG4P130 BO12864-195-HWG4P130 BO12864-221-HWG4P130 BO12864-226-HWG4P130 BO12864-232-HWG4P130 BO12864-241-HWG4P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	4	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SSD1306BZ	4-wire SPI
71		BO12864-214-HBG30P130 BO12864-219-HBG30P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	30	Monochrome (Blue)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1106G	6800/8080 Interface I2C / 4-wire SPI
72		BO12864-18-HWG30P130 BO12864-20-HWG30P130 BO12864-47-HWG30P130 BO12864-54-HWG30P130 BO12864-87-HWG30P130 BO12864-89-HWG30P130 BO12864-92-HWG30P130 BO12864-93-HWG30P130 BO12864-100-HWG30P130 BO12864-104-SWG30P130 BO12864-153-HWG30P130 BO12864-206-HWG30P130	128x64	34.50x23.00x1.43	31.42 x 16.7	29.42 x14.7	30	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1106G	6800/8080 Interface I2C / 4-wire SPI
73	1.32"	BO12896-00-SWG16P132 BO12896-01-SWG16P132	128x96	32.5x29.2x1.76	27.86x27.14	26.86x21.14	16	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SDD1327Z	SPI
74	1.50"	BO128128-01-SWG25P150	128x128	33.90x37.30x1.44	28.855x28.855	26.855x26.855	25	Monochrome (White)	1.65~3.3V	3.5~4.2V	-40~70°C	-40~85°C	SH1107	8-bit 68xx/80xx Parallel, 4-wire SPI, I2C
75	1.54"	BO12864-32-PYG24P154 BO12864-77-PBG24P154 BO12864-138-PWG24P154 BO12864-152-PWG24P154	128x64	42.04x27.22x1.41	37.052 x 19.516	35.052 x17.516	24	Monochrome (Yellow & Blue)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SPD0301ZD	6800/8080 Interface I2C / 4-wire SPI
76		BO12864-165-PWG8P154 BO12864-212-PWG8P154	128x64	42.04x27.22x1.41	37.052 x 19.516	35.052 x17.516	8	Monochrome (White)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SPD0301ZD	6800/8080 Interface I2C / 4-wire SPI
77		BO12864-135-PBG12P154	128x64	42.04x27.22x1.41	37.052 x 19.516	35.052 x17.516	12	Monochrome (Yellow & Blue)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SPD0301ZD	6800/8080 Interface I2C / 4-wire SPI
78		BO12864-150-PWG12P154 BO12864-254-PWG12P154	128x64	42.04x27.22x1.41	37.052 x 19.516	35.052 x17.516	12	Monochrome (White)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SPD0301ZD	6800/8080 Interface I2C / 4-wire SPI
79		BO12864-255-PWG20P154	128x64	42.04x27.22x1.41	37.052 x 19.516	35.052 x17.516	20	Monochrome (White)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SPD0301ZD	6800/8080 Interface I2C / 4-wire SPI

# STANDARD OLED DISPLAY MODULE

Update: 2025/10/16

No.	Size	Bocen Part Number	Resolution	Panel Size (mm)	Viewing Area (mm)	Active Area (mm)	PINs	Color	Porwer Supply Voltage	Driving Voltage	Operating Temperature	Storage Temperature	Drive IC	Interface
80	1.54"	BO12864-217-PWG10P154	128x64	63.00x43.00x7.80	37.05 x 19.52	35.05 x17.52	10	Monochrome (White)	1.65~3.3V	11.5~12.5V	-40~85°C	-45~90°C	SPD0301ZD	I2C
81		BO12864-157-PWG14P154	128x64	42.04x27.22x1.41	37.052 x 19.516	35.052 x17.516	14	Monochrome (White)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SPD0301ZD	6800/8080 Interface I2C / 4-wire SPI
82		BO12864-12-PWG24P154 BO12864-186-PWG24P154 BO12864-203-PWG24P154 BO12864-261-SWG24P154B BO12864-218-SWG24P154	128x64	42.04x27.22x1.41	37.052 x 19.516	35.052 x17.516	24	Monochrome (White)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SPD0301ZD	6800/8080 Interface I2C / 4-wire SPI
83		BO12864-218-SWG24P154	128x64	42.04x27.22x1.41	37.052 x 19.516	35.052 x17.516	24	Monochrome (White)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SSD1309	6800/8080 Interface I2C / 4-wire SPI
84	1.71"	BO12832-11-SWG18P171	128x32	50.50 x 15.75 x 2.00	44.22 x 12.54	42.22 x 10.54	18	Monochrome (White)	2.8~3.3V	11.5~12.5V	-20~70°C	-30~80°C	SSD1307	SPI,I2C
85	2.23"	BO12832-09	128x32	62.00 x 60.00 x 2.01	57.02 x 15.10	55.02 x 13.10	24	Monochrome (White)	2.4~3.5V	12.0~13.0V	-40~70°C	-40~85°C	SSD1305	6800/8080 interface I2C
86		BO12832-10	128x32	62.00 x 60.00 x 2.03	57.02 x 15.10	55.02 x 13.10	24	Monochrome (White)	2.4~3.5V	12.0~13.0V	-40~70°C	-40~85°C	SPD0301	6800/8080 interface I2C
87	2.42"	BO12864-301-SWG24P242	128x64	60.5 x 37 x 1.8	57.01 x 29.49	55.01 x 27.49	24	Monochrome (White)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SSD1309	8-bit 68XX/80XX Parallel, 4-wire SPI, I2C
88		BO12864-302-SWG31P242	128x64	60.5 x 37 x 1.8	57.01 x 29.49	55.01 x 27.49	31	Monochrome (White)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SSD1309	8-bit 68XX/80XX Parallel, 4-wire SPI, I2C
89	2.45"	BO30496-01-HWG30P245	304x96	72 x 28.2 x 1.63	60.86 x 20.78	59.26x19.18	30	Monochrome (White)	1.65~3.5V	11.5~12.5V	-40~70°C	-40~85°C	SH1126	8-bit 8080,8-bit 6800,4-wire SPI,3-wire SPI ,I2C
90	2.7"	BO12864-158-SYG30P270	128x64	73.00 x 71.86 x 2.00	63.41 x 32.69	61.41 x 30.69	30	Monochrome (Yellow)	1.65~3.3V	11.5~12.5V	-40~70°C	-40~85°C	SSD1322	8-bit 68XX/80XX Parallel, 3-/4-wire SP